

MONARCHE'S PAINTS & SOLUTIONS FOR MAINTENANCE, REPAIR, OYBHAUL (MRO) FOR MECHANICAL & ELECTRICAL ENGINEERING



II (1) - Metal Reclamation Putties

Updated on - 1 Mar 15



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	
S.No	Description	Product Name	Code	Pack Size	Pack Size Breakup	COVERAGE - 1 Cm ² / Pack Size / Thickness	COVERAGE - 2 Inch Sq / Pack Size / Thickness	Consumption 2 Inch Sq / Pack Size / Thickness	Basic Price / Pack Size (Rs.)	Excl Duty/EC, SMC @12.5% (Rs.) (on 9)	PRICE (Inclusive of Excl Duty (Rs.) (on 9 + 9))	CST @3% against C Form (Rs.) (on 10)	Insurance @0.2% (Rs.) (on 10+11)	Ex-Works Price with C form Excluding Freight Charge / Entry Tax / Pack Size (Rs.) (10 + 11 + 12)	VAT @14.5% (Rs.) (on 10)	Insurance @0.2% (Rs.) (on 10 + 14)	Ex-Works VAT Price Excluding Freight Charge / Entry Tax / Pack Size (Rs.) (10+11+15)	Material cost / cm2
General Purpose																		
1	Multi-Purpose Reclamation Putty for precision critical jobs - Titanium Putty	SavesPast TP	21101	1 Kg	R 0.800 + H 0.200	796 Cm ² / kg / 5 mm	123.38 Inch ² / kg / 5 mm	0.0081 kg/Sq Inch / 5mm	2636.80	330	2966	59	6	3032	430	6	3402	4
2	Multi-Purpose Reclamation Putty for precision critical jobs - Titanium Putty	SavesPast TP	21101 - A	500 gms	R 0.400 + H 0.100	398 Cm ² / 500 gms / 5 mm	61.69 Inch ² / 500 gms / 5 mm	0.0081 kg / Sq Inch / 5mm	1452.30	182	1634	33	3	1670	237	3	1874	5
3	Multi-Purpose Reclamation Putty for precision critical jobs - Titanium Putty	SavesPast TP	21101 - B	100 gms	R 0.080 + H 0.020	79.6 Cm ² / 100 gms / 5 mm	12.34 Inch ² / 100 gms / 5 mm	0.0081 kg / Sq Inch / 5mm	319.30	40	359	7	1	367	52	1	412	5
4	Extended Pot Life repair applications - Steel Putty	SavesPast SP	21102	1 kg	R 0.800 + H 0.200	770 Cm ² / kg / 5 mm	119.35 Inch ² / kg / 5 mm	0.0084 kg / Sq Inch / 5 mm	2420.50	303	2723	54	5	2783	395	5	3123	4
5	Extended Pot Life repair applications - Steel Putty	SavesPast SP	21102 - A	500 gms	R 0.400 + H 0.100	385 Cm ² / 500 gms / 5 mm	59.68 Inch ² / 500 gms / 5 mm	0.0084 kg / Sq Inch / 5 mm	1339.00	167	1506	30	3	1540	218	3	1728	4
6	Extended Pot Life repair applications - Steel Putty	SavesPast SP	21102 - B	100 gms	R 0.080 + H 0.020	77 Cm ² / 100 gms / 5 mm	11.94 Inch ² / 100 gms / 5 mm	0.0084 kg / Sq Inch / 5 mm	309.00	39	248	7	1	355	50	1	399	5
7	Rebuilding putty for tough wear and abrasion resistance - Ceramic Putty	SavesPast CP	21103	1 Kg	R 0.800 + H 0.200	862 Cm ² / kg / 5 mm	133.61 Inch ² / kg / 5 mm	0.0075 kg / Sq Inch / 5 mm	2660.75	325	2926	59	6	2990	424	6	3356	4
8	Ceramic Carbide Putty against fine particle abrasion - Ceramic Carbide Putty	SavesPast CCP	21104	1 Kg	R 0.800 + H 0.200	624 Cm ² / kg / 5 mm	96.720 Inch ² / kg / 5 mm	0.0103 kg / Sq Inch / 5 mm	4239.30	529	4762	95	10	4867	691	10	5463	3
9	Aluminum based Silicon Carbide Putty against Impact Wear - Ceramic Aluminum Putty	SavesPast CAP	21105	1 Kg	R 0.800 + H 0.200	624 Cm ² / kg / 5 mm	96.720 Inch ² / kg / 5 mm	0.0103 kg / Sq Inch / 5 mm	4573.20	572	5145	103	10	5228	746	10	5901	7
10	Tough rubber like urethane repair compound for wear and impact resistance - Flex Putty	SavesPast FP	21106	500 gms	R 0.333+ H 0.167	1016 Cm ² / 0.5 kg / 2.5 mm	157.48 Inch ² / 0.5 kg / 2.5 mm	0.0032 kg / Sq Inch / 5mm	1421.40	178	1590	32	3	1634	232	3	1834	2
Special Purpose																		
1	Repair of Aluminum parts/coatings - Aluminum Putty	SavesPast AP	21111	500 gms	R 0.400 + H 0.100	507 Cm ² / 0.5 kg / 5 mm	92.635 Inch ² / 0.5 kg / 5 mm	0.0054 kg/Sq Inch / 5 mm	1956.50	238	2144	43	4	2191	311	4	2459	4
2	Repair of Bronze parts / coatings - Bronze Putty	SavesPast BP	21112	500 gms	R 0.250 + H 0.250	428 cm ² / 0.5 kg / 5 mm	66.340 Inch ² / 0.5 kg / 5 mm	0.0075 kg / Sq Inch / 5 mm	2271.15	284	2556	51	5	2611	370	5	2931	7
3	Repair of Copper parts/coatings - Copper Putty	SavesPast CP	21113	500 gms	R 0.400 + H 0.100	507 Cm ² / 0.5 kg / 5 mm	92.340 Inch ² / 0.5 kg / 5 mm	0.0054 kg/Sq Inch / 5 mm	2044.65	256	2300	46	5	2351	334	5	2638	4
4	Repair of Stainless Steel parts/coatings and food processing equipments- Stainless Steel Putty	SavesPast SSP	21114	500 gms	R 0.400 + H 0.100	428 Cm ² / 0.5kg / 5 mm	66.340 Inch ² / 0.5 kg / 5 mm	0.0075 kg / Sq Inch / 5 mm	2971.55	371	3343	67	7	3417	485	7	3834	9
High Temperature Putties Till 230°C																		
1	Rebuilding putty for tough wear and high temperature resistance @ 230°C - High Temp. Ceramic Putty	SavesPast HTCP	21121	1 Kg	R 0.800 + H 0.120	624 Cm ² / kg / 5mm	96.720 Inch ² / kg / 5mm	0.0103 kg / Sq Inch / 5 mm	2997.30	375	3372	67	7	3446	489	7	3868	6
2	Multi-Purpose Reclamation Putty for high temperature resistance @ 230° C - High Temp. Titanium Putty	SavesPast HTP	21122	1 Kg	R 0.930 + H 0.070	624 Cm ² / kg / 5mm	96.720 Inch ² / kg / 5mm	0.0103 kg / Sq Inch / 5 mm	2958.05	314	2822	56	6	2884	409	6	3236	5
Under Pressure Leak Arrest Putties																		
1	Rapid Setting putty for sealing active leakages - Express Titanium Putty	Zero-Down-Time ETP	21131	1 Kg	R 0.5 + H 0.5	1100 Cm ² / kg / 5 mm	170.59 Inch ² / kg / 5 mm	0.0059 kg/Sq Inch/5mm	2543.87	318	2861	57	6	2924	415	6	3282	3
2	Rapid Setting putty for sealing active leakages - Express Titanium Putty	Zero-Down-Time ETP	21131 - A	500 gms	R 0.250 + H 0.250	550 Cm ² / 500 gms / 5 mm	85.25 Inch ² / 500 gms / 5 mm	0.0059 kg/Sq Inch/5mm	1490.80	175	1576	32	3	1611	229	3	1808	3
3	Rapid Setting putty for sealing active leakages - Express Titanium Putty	Zero-Down-Time ETP	21131 - B	100 gms	R 0.050 + H 0.050	110 Cm ² / 100 gms / 5 mm	17.05 Inch ² / 100 gms / 5 mm	0.0059 kg/Sq Inch/5mm	309.00	39	348	7	1	355	50	1	399	4
4	Under water repair putty for chronically wet/damp environments - Under Water Putty	Zero-Down-Time UWP	21132	1 Kg	R 0.5 + H 0.5	862 Cm ² / kg / 5 mm	133.61 Inch ² / kg / 5 mm	0.0075 kg/Sq Inch/5mm	1854.00	232	2066	42	4	2132	302	4	2392	3
5	Under water repair putty for chronically wet/damp environments - Under Water Putty	Zero-Down-Time UWP	21132 - A	500 gms	R 0.250 + H 0.250	431 Cm ² / 500 gms / 5 mm	66.81 Inch ² / 500 gms / 5 mm	0.0075 kg/Sq Inch/5mm	1019.70	127	1147	23	2	1172	166	2	1316	3
6	Under water repair putty for chronically wet/damp environments - Under Water Putty	Zero-Down-Time UWP	21132 - B	100 gms	R 0.050 + H 0.050	86.2 Cm ² / 100 gms / 5 mm	13.36 Inch ² / 100 gms / 5 mm	0.0075 kg/Sq Inch/5mm	228.60	28	255	5	1	261	37	1	292	3
Accessories																		
1	For Cleaning of surfaces before Epoxy Putty Application - Cleaner	SavesPast ACR	21141	1 Kg	Single Component	N/A	N/A	N/A	618.00	77	695	14	1	711	101	1	797	0
2	Glass Fibre Cloth for Additional Strength - Reinforcement Tape	SavesPast ART	21142	5.5 m (Roll)	Single Component	N/A	N/A	N/A	386.25	48	435	9	1	444	63	1	498	0
3	Prevents Bonding of Epoxy Putty - Release Agent	SavesPast ARA	21143	114 gms	Single Component	N/A	N/A	N/A	180.25	23	203	4	0	207	29	0	233	0
4	Mixing & Application tool for Putty Application - Mortar	SavesPast AMK	21144	1 No	Single Component	N/A	N/A	N/A	103.00	13	118	2	0	118	17	0	133	0
5	For Priming of Metal Surfaces before SavesPast FP Application - Metal Primer	SavesPast AMP	21145	114 gms	Single Component	N/A	N/A	N/A	206.00	26	232	5	0	237	34	0	266	0
6	For Priming of Rubber Surfaces before SavesPast FP Application - Rubber Primer	SavesPast ARP	21146	114 gms	Single Component	N/A	N/A	N/A	206.00	26	232	5	0	237	34	0	266	0
7	For Accelerating Cure time of SavesPast FP - Flex Accelerator	SavesPast AFA	21147	50 gms	Single Component	N/A	N/A	N/A	257.50	32	290	6	1	296	42	1	332	0

Abbreviations R - Resin H - Hardener